


Galvanised Malleable Reducing Socket



Galvanised Malleable Reducing Socket			
AAP CODE	IMPERIAL SIZE	A	APPROX KG/PC
LS1008	3/8 X 1/4	28.7	0.05
LS1508	1/2 X 1/4	31.8	0.05
LS1510	1/2 X 3/8	31.8	0.07
LS2008	3/4 X 1/4	36.6	0.09
LS2010	3/4 X 3/8	36.6	0.10
LS2015	3/4 X 1/2	36.6	0.11
LS2510	1 X 3/8	42.9	0.16
LS2515	1 X 1/2	42.9	0.16
LS2520	1 X 3/4	42.9	0.18
LS3215	1-1/4 X 1/2	52.3	0.24
LS3220	1-1/4 X 3/4	52.3	0.26
LS3225	1-1/4 X 1	52.3	0.28
LS4015	1-1/2 X 1/2	58.7	0.31
LS4020	1-1/2 X 3/4	58.7	0.32
LS4025	1-1/2 X 1	58.7	0.35
LS4032	1-1/2 X 1-1/4	58.7	0.39
LS5015	2 X 1/2	71.4	0.52
LS5020	2 X 3/4	71.4	0.52
LS5025	2 X 1	71.4	0.55
LS5032	2 X 1-1/4	71.4	0.54
LS5040	2 X 1-1/2	71.4	0.62
LS6525	2-1/2 X 1	82.6	0.89
LS6532	2-1/2 X 1-1/4	82.6	0.93
LS6540	2-1/2 X 1-1/2	82.6	0.94
LS6550	2-1/2 X 2	82.6	1.01
LS8025	3 X 1	93.7	1.39
LS8032	3 X 1-1/4	93.7	1.40
LS8040	3 X 1-1/2	93.7	1.47
LS8050	3 X 2	93.7	1.50
LS8065	3 X 2-1/2	93.7	1.61
LS9450	4 X 2	111.3	2.52
LS9465	4 X 2-1/2	111.3	2.68
LS9480	4 X 3	111.3	2.74