

Hiflex / Marineflex Light Corrugated Suction



Smooth bore lightweight suction hose well suited as an open ended discharge hose for bilge pumps, pond pumps and commonly used as a waste hose for caravans or RV's.

Conforms to AS/NZS 2070 (plastics for food contact).

Product Code	Diameter (mm)		Working Pressure (psi)	Minimum Bend Radius [mm]	Vacuum Rating (mm hg)	Roll Length (m)
	ID	OD				
SHHIFLEX2	19.0	24.7	29	90	310	20
SHHIFLEX2	25.0	31.1	29	95	310	20
SHHIFLEX2	28.0	34.9	29	105	310	10, 20
SHHIFLEX3	32.0	38.9	29	115	310	20
SHHIFLEX3	38.0	44.9	29	140	310	20
SHHIFLEX5	50.0	56.9	29	180	310	20

(NON TOXIC FOOD GRADE: AS / NZS 2070)



Grey Suction



Premium quality general purpose hose well suited for use with water, mud, grain, sand and some chemicals. Good abrasion resistance and excellent U.V. stability.

Conforms to AS/NZS 2070 (Plastics for food contact).

Outstanding U.V. stability.

Temperature: -5C to +60C.

Product Code	Diameter (mm)		Working Pressure (psi)	Weight (kg/m)	Minimum Bend Radius (mm)	Roll Length (m)
	ID	OD				
SHHD025	25.0	31.9	130	0.39	120	20
SHHD032	32.0	39.4	116	0.53	150	20
SHHD038	38.0	46.1	101	0.69	200	20, 30
SHHD044	44.0	52.6	87	0.89	250	20
SHHD050	51.0	60.2	87	1.07	300	20, 30
SHHD063	63.0	74.4	87	1.51	400	20
SHHD075	76.0	89.6	73	2.25	450	20
SHHD100	102.0	116.0	58	3.17	600	20

(NON TOXIC FOOD GRADE: AS / NZS 2070)

