



Pro-Loc™ Tape Fittings



Easy to Spot. Tough to Beat.

Easy to install Pro-Loc tape fittings offer a comprehensive range of configurations including couplings, layflat take-offs and valve options. Engineered for use with quality 16mm and 22mm tape, Pro-Loc fittings are designed to last for the life of the irrigation system.

Features and Benefits:














Pro-Loc tape fittings deliver the quality you expect from Toro for reliable performance, season after season.









- Tight Seal - Coarse thread ensures a tight seal, even in dirty conditions.
- Easy to Install - Long double barb for positive installation.
- Easy to Grip - Ergonomically designed nut provides a secure connection every time.
- Easy to See - Bright blue nut makes tape fittings easy to find, remove and reuse.
- Low Profile - Compact design doesn't interfere with retrieving the tape.
- UV Resistant - Tough anti-UV stabiliser to suit Australian conditions.

Designed for reliable, proven results when used with Aqua-Traxx™, Pro-Loc fittings are also suitable for use with other leading tape brands. For optimal performance, use Pro-Loc in conjunction with PC Aqua-Traxx - Australia's only premium control drip tape available exclusively from Toro Australia.



Pro-Loc™ Tape Fittings


Couplings		
	FTC500	16mm Tape Coupling
	FTC700	22mm Tape Coupling
	FTC800	25mm Tape Coupling
Barb Takeoffs		
	FTA5-250B	16mm Tape x Barbed Takeoff (suit 101P4 Punch / 4.5mm hole)
	FTA5-400B	16mm Tape x Barbed Takeoff (suit 7.5mm hole)
	FTA5-700B	16mm Tape x Barbed Takeoff (suit 13mm hole)
	FTA7-700B	22mm Tape x Barbed Takeoff (suit 13mm hole)
	FTA5-425G	16mm Tape x Barbed Takeoff with Integral Gasket (requires 11.5mm hole)
	FTA5-425GR	16mm Tape x Barbed Takeoff with Rubber Grommet*
	FTA7-425GR	22mm Tape x Barbed Takeoff with Rubber Grommet*
Threaded Adaptors		
	FTA5-75MPT	16mm Tape x 3/4" MBSP Adaptor
	FTA7-75MPT	22mm Tape x 3/4" MBSP Male Adaptor
	FTA5-75FHS	16mm Tape x 20mm Female Hose Swivel Adaptor
Flush Valves		
	FFVFPT-L	Automatic Flush Valve x 20mm Female Low Flow - White
	FFVFPT-H	Automatic Flush Valve x 20mm Female High Flow - Red
	FTA5-FVL	16mm Tape x Low Pressure Flush Valve
	FTA7-FVL	22mm Tape x Low Pressure Flush Valve
Layflat Takeoff Fittings		
	FTA5-LF	16mm Tape x Layflat Takeoff - Single Grip**
	FTA7-LF	22mm Tape x Layflat Takeoff - Single Grip**
Barbed Adaptors		
	FTA5-500HB	16mm Tape x 16mm OD tube Barbed Adaptor
	FTA5-700HB	16mm Tape x 20mm OD tube Barbed Adaptor
	FTA7-700HB	22mm Tape x 20mm OD tube Barbed Adaptor
Tees		
	FTT500	16mm Tape Tee
	FTT700	22mm Tape Tee

Barbed Tees		
	FTT5-500HB	16mm Tape x 16mm OD tube Barbed Tee
	FTT5-700HB	16mm Tape x 20mm OD tube Barbed Tee
Shutoff Valves		
	FTV500	16mm Tape Shutoff Valve
	FTV700	22mm Tape Shutoff Valve
Barbed Shutoff Valve with Locking Nut		
	FTV5-420BN	16mm Tape x Barb (suit 10mm hole) with Locking Nut Shutoff Valve
	FTV7-500HN	22mm Tape x 16mm OD tube Barb with Locking Nut Shutoff Valve
Barbed Shutoff Valves		
	FTV5-500HB	16mm Tape x 16mm OD tube Barbed Shutoff Valve
	FTV7-500HB	22mm Tape x 16mm OD tube Barbed Shutoff Valve
	FTV5-250B	16mm Tape x Barbed Shutoff Valve (suit 101P4 Punch / 4.5mm hole)
	FTV5-400B	16mm Tape x Barbed Shutoff Valve (suit 7.5mm hole)
Layflat Takeoff Shutoff Valves		
	FTV5-LF	16mm Tape x Layflat Takeoff Shutoff Valve - Single Grip **
	FTV7-LF	22mm Tape x Layflat Takeoff Shutoff Valve - Single Grip **
T-Handle Hex Tool		
	LF-INST	T-Handle Hex Tool for Layflat Installation

* 15mm or 0.59" drill size

** requires a 16mm layflat punch *** 16mm or 0.63" drill size


Pro-Loc™ Fittings vs Tube Selection Guide		
Code	Tube Inner Diameter Tolerance (mm)	Wall Thickness Tolerance (mm)
FTA5-500HB FTT5-500HB FTV500 FTV7-500HN FTV5-500HB FTV7-500HB	13.2 - 15.0	0.50 - 1.40
FTA5-700B FTA7-700B FTA5-700HB FTA7-700HB FTT5-700HB FTV700	17.2 - 18.5	0.80 - 1.40



Layflat to Aquatraxx Offtake**




PVC to Aquatraxx Offtake*



PVC to Aquatraxx Offtake***



LD Poly to Aquatraxx Offtake



LD Poly to Aquatraxx Offtake

For more information, please phone
1300 130 898 or visit www.toro.com.au

 Toro Australia Pty Ltd