

TECHLINE[™] AS

HEAVY WALL, PRESSURE COMPENSATING 13mm BROWN DRIPPERLINE

APPLICATIONS

• Domestic & light commercial surface and sub-surface applications

FEATURES AND BENEFITS

- Patented TurboNet[™] Dripper Technology
- Pressure compensated dripper self regulates drip discharge over large pressure variation
- Anti-siphon mechanism prevents suck back in to dripper
- · Centrally mounted dripper with large inlet filter
- Mechanical root barrier
- Approved by the Smart WaterMark ™

SPECIFICATIONS

- Pressure compensated (PC) and Anti-Siphon (AS) dripperline
- Operating Pressure: 40 kPa 250 kPa
- Recommended filtration: 120 mesh (130 micron)
- Tubing colour: co-extruded brown tube
- UV resistant Low Density Polyethyline (LDPE)
- Additional flow rates, spacings and pipe sizes are available on request. Minimum quantities apply.

DRIPPER TECHNICAL DATA

INSIDE DIAMETER (MM)	OUTSIDE DIAMETER (MM)	DRIPPER FLOW RATE (L/H)	DRIPPER SPACING (M)	PRESSURE RANGE (kPa)	COIL LENGTH (M)
12.9	15.3	<mark>1.6</mark> & 3.0	<mark>0.3</mark> & 0.4	40 - 250	50 <mark>, 100</mark> & 200

TECHNICAL DATA

Maximum run length (m) on flat ground (based on 5% flow variation)

NOMINAL FLOW RATE (L/H)	50 kPa	100 kPa	150 kPa	200 kPa	250 kPa
1.6 l/h @ 0.3m	40m	<mark>73m</mark>	90m	(100m)	(110m)
3.0 l/h @ 0.3m	26m	48m	60m	67m	73m
1.6 l/h @ 0.4m	50m	93m	115m	130m	143m

SUITABLE FITTINGS

SAP	DESCRIPTION	SAP	DESCRIPTION
00005-003450	13mm Straight Take-off to suit LDPE	00005-004100	13mm Elbow
00005-011400	13mm Elbow Take-off to suit LDPE	00005-005300	13mm Tee
45000-001650	7mm Professional Punch Tool	00005-003500	13mm Joiner
00005-009000	13mm Straight Take-off to suit PVC	00005-003100	13mm End Plug
00005-009300	13mm Grommet (16mm hole saw)	00005-001900	13mm Ratchet Clamp
00025-002400	Hold Down Stake (Asta)	00060-002200	13mm Cobra Clamp (C15/8 White)

For more information, please contact Netafim at www.netafim.com.au





