

Description:

Sulfuric acid-based drain opener. Designed to quickly dissolve all organic obstructions such as cloth, paper, rags, grease, hair, paper, sanitary napkins, styrofoam, sludge, soap, and coffee grounds. Use in floor drains, sink drains, tub drains, shower drains, and other drains prone to clogging.

Benefits:

- Removes lime scale and rust deposits from drains and traps
- Safe for use in metal or PVC plumbing systems
- Inhibited to prevent flash rusting
- Will not harm septic tank activity



Application:

Add the required amount of Mo-Flo as per chart below. Always use face shield when applying. Keep face and hands to one side of drain - do not look into drain while adding Mo-Flo.

	Quantity to be used	Contact Time	Additional Recommendations
Small Clogged drains	250 ml	5 minutes	Flush with water 2 to 3 minutes
3 to 4 inch drains	1 Litre	15 minutes	Flush with water 5 minutes
6 to 8 inch drains	2 Litres	15 minutes	Flush with water 15 minutes
Grease Traps	2 Litres	45 minutes	Use 20-30% of initial application periodically for maintenance
Slop Sinks	1 Litre	25 minutes	Pour directly into drain
Cesspools	4 Litres	60 minutes	Insert through hose to bottom of pool

NOTE: Quantity to use may vary depending upon conditions and size. Do not allow to stand on porcelain surfaces as heat build-up may cause cracking. Do not use hot water immediately before or after using Mo-Flo. Use cold water only. Use in well ventilated area only.

Specifications:

pH <1
 Density @ 25°C (ASTM-D-287) 1.8gm/Ltr
 Colour Black
 Appearance Viscous Liquid
 Odour No Odour
 Health/Flammability/Reactivity 3/0/2
 Personal Protection C

