

Product Specifications

Hunter XC Controller

SPECIFICATIONS & FEATURES

- ❖ Outdoor models, built in transformer with 3 pin plugs
- ❖ 3 programs, A, B, C
- ❖ Start times: 4 per day, per program for up to 12 daily starts
- ❖ Station run time: 0 minutes to 4 hours in 1-minute increments
- ❖ Day schedule: 7-day calendar true odd/even programming with 365-day calendar clock, or interval watering (up to 31days)
- ❖ AM/PM or 24 hour clock option
- ❖ Automated chronological ordering of start times/start time stacking
- ❖ One-button manual start and advance
- ❖ Seasonal adjust: 0% to 150%
- ❖ Transformer input: 240VAC, 60 Hz (domestic model)
- ❖ Transformer output: 24VAC, 1.0 amps (capable of operating equivalent of 3 solenoids simultaneously)
- ❖ Station output: .56 amps
- ❖ Electronic short circuit detection
- ❖ Battery: 3V lithium (included) for remote programming and timekeeping, not required for program backup
- ❖ Programmable delay between stations
- ❖ Rain sensor bypass switch compatible with micro switch based sensors, displays when sensor is active
- ❖ Programmable sensor input by station
- ❖ Original program can be saved in non-volatile memory and retrieved later if needed
- ❖ Programmable rain delay from 1 to 7 days
- ❖ Programmable event day off allows specific day(s) to be designated as always “off”
- ❖ Hunter Quick Check™ helps troubleshoot field wiring issues
- ❖ Test program feature allows for quick system checks
- ❖ UL Listed/CE Approved

